

MANUAL EVENROLL ROPE & PULLEY

CEILING- OR WALL-MOUNTED, FREE-HANGING



- The Evenroll Rope & Pulley wall- or ceiling-mounted, projection screen utilizes a nylon marine pulley system. Flanged spools keep the cords tracking properly and provide smooth operation and performance. It installs easily making it ideal for gymnasiums, auditoriums, or other large venues.

Simplicity of operation and no wiring set-up or cost. Free-hanging, fiberglass-backed projection screens maintain flatness thanks to the weight of the screen and bottom dowel.

FEATURES

- Optional wall mounting brackets, formed of ¼" (6 mm) strap steel, extends projection screen 12" (30 cm) from the wall.
- Rope and pulley system utilizes nylon marine pulleys and flanged spools for smooth operation.
- Installs easily to wall or ceiling.
- Cable clamp provided to stop screen at desired level.
- WARRANTY: One year against defects in materials and workmanship.

OPTIONS

- **Viewing Surfaces:** OptiView™ (self-supporting) family.

SUPPORTING DOCUMENTS

All instructions, technical drawings and other supporting documents are located at: draperinc.com/Documents.aspx

SIZES

- **Maximum fabric width** up to 24' (732 cm) wide.
- 2.35:1 FORMAT: 15' 4" (467 cm) to 26' 2" (798 cm) diagonal.
- 16:9 FORMAT: 16' 4" (497 cm) to 27' 6" (838 cm) diagonal.
- 4:3 FORMAT: 17' 6" (533 cm) to 25' (762 cm) diagonal.
- AV FORMAT: 14' x 14' (427 cm x 427 cm) to 24' x 24' (731 cm x 731 cm) viewing area.
- Custom sizes available including 16:10.

For more information on this product visit:

draperinc.com/projectionscreens/manualscreens.aspx